

# Reattori

ELETRONICI



REATTORI ELETTRONICI

**PROMITALIA**

Corso Vittorio Emanuele 419 - 97013 Comiso (RG) Tel: 0932 966955 348 3336570 Fax: 0932 1842001  
e-mail: promitalia@promitalia.net office@promitalia.net www.promitalia.net

REATTORI ELETTRONICI



- AC voltage range [min-max] 176-264V
- DC voltage range [min-max] 198-276V
- High Luminous Factor: 95%
- Operating frequency  $\geq$  40Hz
- Suitable for Automatic or manual wiring
- Suitable for use in emergency lighting
- Safe switch off of defective lamps
- Automatic re-start after lamp change
- Protection against lamp open circuit
- Protection against lamp fault condition [including to the end of lamp life]
- Auto-terminal.

Certified  
 EN55015  
 EN61547  
 EN61347-1  
 EN61347-2-3  
 EN60925  
 EN60929  
 EN61000-3-2

in accordance  
 with VDE 0108  
 IEC 68-2-64 Fh  
 IEC 68-2-29 Eb  
 IEC 68-2-30

■ Reattori elettronici di alta qualità

1 x 1 neon  
 1 x 2 neon  
 1 x 3 neon  
 1 x 4 neon

Articolo	W	V	Hz	Dimensioni L x W x H	230 V / 50 Hz mA	Power Factor	Total Harmonic Distortion	Current Crest Factor	Temperature Range °C	Tc point °C
E 118H	1X18W	220V-240V	0/50/60Hz	274X27X27	80	0,98	<20%	<1,7	-25 +50	70
E 130H	1X30W	220V-240V	0/50/60Hz	274X27X27	133	0,98	<20%	<1,7	-25 +50	70
E 136H	1X36W	220V-240V	0/50/60Hz	274X27X27	160	0,98	<20%	<1,7	-25 +50	70
E 158H	1X58W	220V-240V	0/50/60Hz	320X33X28	257	0,98	<20%	<1,7	-25 +50	70
E 218H	2X18W	220V-240V	0/50/60Hz	274X27X27	160	0,98	<20%	<1,7	-25 +50	70
E 230H	2X30W	220V-240V	0/50/60Hz	320X33X28	266	0,98	<20%	<1,7	-25 +50	70
E 236H	2X36W	220V-240V	0/50/60Hz	320X33X28	320	0,98	<20%	<1,7	-25 +50	75
E 258H	2X58W	220V-240V	0/50/60Hz	320X33X28	514	0,98	<20%	<1,7	-25 +50	75
E 318H	3X18W	220V-240V	0/50/60Hz	336X33X28	240	0,98	<20%	<1,7	-25 +50	70
E 330H	3X30W	220V-240V	0/50/60Hz	336X33X28	399	0,98	<20%	<1,7	-25 +50	70
E 336H	3X36W	220V-240V	0/50/60Hz	336X33X28	479	0,98	<20%	<1,7	-25 +50	70
E 418H	4X18W	220V-240V	0/50/60Hz	336X33X28	319	0,98	<20%	<1,7	-25 +50	70
E 430H	4X30W	220V-240V	0/50/60Hz	336X33X28	532	0,98	<20%	<1,7	-25 +50	70
E 436H	4X36W	220V-240V	0/50/60Hz	336X33X28	639	0,98	<20%	<1,7	-25 +50	70



